


T-1600 by TRAK Kayaks

Based on an adjustable hull shape set to a moderate rocker.

Paddler Weight	150 lbs	200 lbs	150 lbs	200 lbs
Cargo weight	none	none	100 lbs	100 lbs
Waterline length	15.06	15.18	15.30	15.39
Waterline beam	1.65	1.68	1.70	1.73
Draft	0.35	0.41	0.46	0.50
Prismatic coefficient	0.47	0.49	0.50	0.51
Block coefficient	0.36	0.38	0.40	0.41
Wetted surface in sq.ft.	19.50	21.30	22.99	24.63
Pounds to immerse one inch	78.30	81.30	83.71	85.98
Effective waterline length			14.78	
Volume, cu.ft.			12.06	
Center of buoyancy, % of length from bow			51.26	
Metric equivalents				
Paddler Weight	68.04 kg	90.72 kg	68.04 kg	90.72 kg
Cargo weight	none	none	45.46 kg	45.46 kg
Waterline length	4.59	4.63	4.66	4.69
Waterline beam	0.50	0.51	0.52	0.53
Draft	0.11	0.12	0.14	0.15
Prismatic coefficient	0.47	0.49	0.50	0.51
Block coefficient	0.36	0.38	0.40	0.41
Wetted surface in sq.meters	1.81	1.98	2.14	2.29
Kgs to immerse 2.54 cm	35.52	36.88	37.97	39.00
Effective waterline length			4.50	
Volume cubic meters			0.34	

Righting/Heeling Moments (Fixed-weight)



Stability Curves

1. 150 lb. paddler, no cargo
2. 200 lb. paddler, no cargo
3. 150 lb. paddler, 100 lb. cargo
4. 200 lb. paddler, 100 lb. cargo

Length overall in decimal ft	16.35
Beam in inches	22.38
Volume in cu.ft.	12.06
Cockpit width in inches	15.75
Cockpit length in inches	30.75
Coaming height forward, inches	10.00
Coaming height aft, inches	9.00
Height of seat in inches	1.63
Weight in pounds	51.50
Metric Equivalents	
Length overall in meters	4.98
Beam in meters	0.57
Volume in kiloliters	0.34
Cockpit width, cm	40.01
Cockpit length, cm	78.11
Coaming height forward, cm	25.40
Coaming height aft, cm	22.86
Height of seat, cm	4.13
Weight in kg	23.36