


# Aquanaut RM

by Valley Canoe Products

Paddler Weight	150 lbs	200 lbs	150 lbs	200 lbs
Cargo weight	none	none	100 lbs	100 lbs
Waterline length	14.51	14.74	14.95	15.09
Waterline beam	1.75	1.79	1.82	1.84
Draft	0.33	0.38	0.42	0.47
Prismatic coefficient	0.55	0.56	0.56	0.57
Block coefficient	0.40	0.42	0.43	0.44
Wetted surface in sq.ft.	19.05	20.68	22.17	23.59
Pounds to immerse one inch	87.41	91.83	95.22	97.98
Effective waterline length			14.95	
Volume, cu.ft.			13.43	
Center of buoyancy, % of length from bow			49.90	
<b>Metric equivalents</b>				
Paddler Weight	68.04 kg	90.72 kg	68.04 kg	90.72 kg
Cargo weight	none	none	45.46 kg	45.46 kg
Waterline length	4.42	4.49	4.56	4.60
Waterline beam	0.53	0.54	0.55	0.56
Draft	0.10	0.12	0.13	0.14
Prismatic coefficient	0.55	0.56	0.56	0.57
Block coefficient	0.40	0.42	0.43	0.44
Wetted surface in sq.meters	1.77	1.92	2.06	2.19
Kgs to immerse 2.54 cm	39.65	41.65	43.19	44.44
Effective waterline length			4.56	
Volume cubic meters			0.38	

Righting/Heeling Moments (Fixed-weight)



Stability Curves

1. 150 lb. paddler, no cargo
2. 200 lb. paddler, no cargo
3. 150 lb. paddler, 100 lb. cargo
4. 200 lb. paddler, 100 lb. cargo

Measurements	
Length overall in decimal ft	17.11
Beam in inches	22.50
Volume in cu.ft.	13.43
Cockpit width in inches	15.00
Cockpit length in inches	29.38
Coaming height forward, inches	11.75
Coaming height aft, inches	8.00
Height of seat in inches	1.25
Weight in pounds	67.25
Metric Equivalents	
Length overall in meters	5.22
Beam in meters	0.57
Volume in kiloliters	0.38
Cockpit width, cm	38.10
Cockpit length, cm	74.61
Coaming height forward, cm	29.85
Coaming height aft, cm	20.32
Height of seat, cm	3.18
Weight in kg	30.50